

USER GUIDE FOR GLAMOUR PANEL







INSTRUCTION MANUAL





Leksa Lighting® all rights reserved, Information, Specifications, Images and Instructions given in the document herein subject to change without further notice. Leksa Lighting Logo, Data and Indicated product names, Model no's herein the trademarks of Leksa Lighting.

You may connect to below contact for your queries:

- biz@leksalighting.com
- www.leksalighting.com
- © +91-7899 543210

For Quality and Service support reach us @ quality@leksalighting.com

Important Notice:

There are no user serviceable parts inside the fixture. Do not attempt any repairs yourself; doing so will cease the manufacturing warranty and such acts will void the manufacturer warranty claims.

- Warranty claims to be reported to the above referred email ID's with the product SI. Nos.
- > Warranty will not be extended on the glass and breakable items like lenses etc.
- > Product warranty does not cover the physical damages, breakages etc.
- Product warranty ceases if the product is not used as per manufacturer instructions.
- Product warranty is limited to the functional aspects of the fixture.
- Repair or Replacement is depending on the variance of complaint subject to manufacturer decision.

INSTRUCTION MANUAL





Instructions:

This Product is IP20 rated. For proper operation, follow the **Installation guidelines described in this manual. Only qualified and** certified personnel should perform the installation and only the original rigging parts (brackets, holders, clamps, safety cables) included with this fixture should be used for installation. Any modifications will void the original manufactures warranty and increase the risk of damage and/or personal injury.


- Never look directly into the light source to prevent risk of injury to your retina, which may induce blindness. Those suffering from EPILEPSY should avoid looking directly into the light source of this unit at all times.
- ➤ The fan and air inlets must remain clean and never blocked. Allow approx. 6" (15cm) between this fixture and other devices or a wall for proper cooling.
- Always disconnect from main power source before performing any type of service and/or cleaning procedure. Only handle the power cord by the plug end, never pull by tugging the wire portion of the cord.
- ➤ Do NOT operate fixture if the power cord has become frayed, crimped and/or damaged. If the power cord is damaged, replace it immediately with a new one of similar power rating.
- Do NOT operate fixture near any flammable materials.
- Do NOT operate fixture in dusty environments.
- Fixture is IP20 rated and should be operated at the dry spaces. Fixture may get damaged to moistures and wet environments.
- ➤ This fixture has an inbuilt signal dimming system. Do NOT connect this fixture for external dimmer packs.
- We urge you to ensure proper mechanical fitments of clamps and a usage of safety chains while suspending from the top.




FIXTURE OVERVIEW:



DMX Input 5 Pin XLR Socket



DMX Output 5 Pin XLR Socket



1	Ground	2	Data -	3	Data +
4	Open	5	Open		

Note:

- ➤ DMX 512 Signal looping can be done from one fixture to other.
- Maximum 25 to 30 Fixtures can be taken in a single loop provided the distance is within short range.
- ➤ No Y Split is allowed for DMX looping.
- > DMX last open end to be terminated with a 120 Ohm Resistor termination plug







FIXTURE DETAILS:

Type of Fixture : LED GLAMOUR PANEL Lamp Source : Light Emitting Diode (LED)

Input Voltage : 110-240V, 50-60Hz

Power Consumptions : LED GLAMOUR PANEL – 300W

Control Modes : Manual/DMX

Power Chord : Neutrik Power In & Loop

DMX Interface : 5 Pin (Standard), 3 Pin (Custom)

IP Rating : IP 20

Dimensions : 550 x 150 x 395 mm (LxBxH)

Weight : 12 Kg

Note:

For Further assistance, you are requested to contact our office or authorized dealers. We are there at your service.

Thank You for Choosing Leksa Lighting:

Leksa Lighting Technologies Pvt. Ltd.
Ashwathapura Road, Moodbidri,
Mangalore – 574227, India
www.leksalighting.com
biz@leksalighting.com
+91-7899 543210