# www.leksalighting.com



### 19x15W LED Moving Head Wash

### Product Code Product Description

: LK MH 1915WSH : Moving Head Zoom Wash

Multipurpose motorised LED Moving Head zoom wash light with excellent output and throw used specially for effect lighting needs. Light has a set of inbuilt effect functions and can also controlled and edited with the external lighting console. Moving Head wash is used for Stage Lighting, DJ Effects, Events and multipurpose venues.

Lamp Source	:	19x15W LED, RGBW
Electrical	:	AC 110-240V, 50/60HZ
Mode	:	13/16 Channel DmX Control, Stand Alone, Auto Run & Master Slav



### Features:

- High Bright Daylight Open Colour
- Pan Range 540° & Tilt Range 270°
- 16 Bit High Precision Movement
- Auto Pan-tilt correction
- Zoom : 6°~60°
- Power consumption: 300W
- Control options : DMX, stand-alone scene
- Wash + Zoom double function
- Electronic Dimming: 0 100%
- Strobe and pulse effects : Variable speed and action
- Variable Colour Mixing and temperatures
- Lumens output : 2000
- LED lifetime: 50,000 hours
- LCD Easy view display
- Data DmX through 3 / 5 Pin XLR's
- IP20 rated product
- Firmware Upgrade Option
- Low noise Fans, Low dB levels
- Body made of hear proof Plastic & Alloy
- Product size: 380\*260\*475mm
- Net weight: 7.5kgs

We Innovate Continuously. Hence the data and details subject to change without any further notice.



# 19x15W Moving Head Wash – DMX CHANNELS

CH 1 – Strobe

CH 4 – X axis

CH 7 - Y-axis fine adjustment

CH 10 – LEDR Dimming

CH 13 – LEDW Dimming

CH 2 – Total Dimming

CH 5 – X-axis fine adjustment

CH 8 – Reset

CH 11 –LEDG Dimming

CH 14 – Color temperature CTO CH 3 - Focusing

CH 6 – Y-axis

CH 9 – Color Display

CH 12 – LEDB Dimming

### **Technical Specifications:**

#### Electrical

- Power supply: Electronic auto-ranging
- Input voltage range: Supply 100-240V, 50/60Hz
- Rated Power : 300W
- Strobe Rate: 0 to 25K Hz
- High-speed strobe: 0-30 times/sec

### Operation

- · Silent fans cooling
- Light source life: 20000 hours
- Stand-alone operation
- International standard DMX512. With RDM function



**Available Models:** 

- LK MH 60S
- LK MH 150S
- LK MH 200S
- LK MH 350 BSW

We Innovate Continuously. Hence the data and details subject to change without any further notice.