www.leksalighting.com



Product Code : LK MH 200S

Product Description : Moving Head Spot – 200W LED

Specifically designed for all entertainment show purposes, this high-brightness motorized LED moving head spot light has a long throw distance and exceptional output, including color mixing, strobe effects, motorized zoom, gobos, and integrated programs for automated lighting sequences, are frequently included with LED moving heads. With lighting consoles or software, LED moving heads may be manually controlled via DMX protocol, giving exact control over color, intensity, movement, and effects.

Lamp Source : 200W Chip On Board Daylight White LED

Electrical : AC 90-260V, 50/60HZ

Mode : 17 Channel DmX Control, USITT DMX 512

Stand Alone, Test Mode & Master Slave

200W LED Moving Head



Technical Specifications:



Motorized

- Pan/Tilt
- Pan movement range: 540°
- Tilt movement range: 270°
- · Automatic Pan/Tilt position correction

Optic:

- · High Bright Daylight Open Colour
- Beam Angle 13°, focus function
- Dimmer: Smooth dimmer from 0-100%
- · Color Wheel: 7 colors +white
- 1 static Gobo Wheel: 8 gobos +white
- · 1 Rotation Gobo Wheel: 6 gobos +white
- Prism: 3-facet Prism
- Bi-directional rotatable at variable speeds
- High speed strobe effect with 1-25 flashers per second

Other

- Colorful LCD display
- 3-pin & 5-pin XLR connectors IN/OUT
- IP20 rated product
- Efficient low noise fan cooling system
- Power Con IN / OUT
- Body made of hear proof Plastic & Alloy
- Dimensions: 328*220*482mm
- Net Weight: 12.25kg



200W Moving Head – DMX CHANNELS

CH 1 - Pan

CH 4 - Tilt Fine

CH 7 - LED Strobe

CH 10 – 8 Static Gobos +

White

CH 13 - Focus

CH 16 – Self Setting Program

CH 2 - Pan Fine

CH 5 - X, Y Speed

CH 8 – 7 Color + White

CH 11 – 6 Rotation Gobos

+ White

CH 14 – Prism

CH 17 - Reset

CH 3 - Tilt

CH 6 - LED Dimmer

CH 9 - Color Effect

CH 12 - Gobo Rotation

CH 15 - Prism Rotation

Technical Specifications:

Electrical

Power supply: Electronic auto-ranging

Input voltage range: Supply 90-260V, 50/60Hz

Power consumption: 315W

· High speed strobe effect

Light Source: 200W High Output White LED

Two 1/4 turn fastening Omega Clamps

Control Signal: DMX 512, master-slave

Operation

- Built-in demo sequences
- Silent fans cooling
- · Strong three-phase motors
- Stand-alone operation







Available Models:

- LK MH 60S
- LK MH 150S
- LK MH 350 BSW
- LK MH 400 BSW