

230W Moving Head 7R Beam

Product Code : LK MH 7R
Product Description : Moving Head Beam – 7R

Moving Head Beam effect light 7R Base high bright strong beam, ideal for Stage Events, Auditorium Stages, Multipurpose application. Quick response to the control signal makes it unique. Excellent zoom range for beam angle varying from 0° ~ 5° to create effect of beam function.



Lamp Source : MSD Yodn Lamp 230W 7R
Electrical : AC 100-240V, 50/60HZ
Mode : 16 / 20 Channel DmX Control, Stand Alone, Test Mode & Master Slave

Technical Specifications:

Optic:

- Dimmer: 0~100% linear dimmer
- Foggy: 0~100% linear foggy
- Color Wheel: 14 colors + open
- Gobo Wheel: 17 gobos + open
- Prism: 16-facet prism
- Optical Device: three lens group, 0~5°
- Strobe: Double patch strobe maximum reaches 13 times per second

Motorized

- Pan/Tilt
- Pan scanning: 540°(16bit scanning accuracy)
Tilt scanning: 270°(16bit scanning accuracy)
Automatic Pan/Tilt position correction

Other

- Display: LCD display board
- Data DmX through 3 / 5 Pin XLR's
- IP20 rated product
- Efficient low noise fan cooling system
- International Standard DMX 512
- Housing: Black (white color for optional)
Overheating intelligent protection
- Gross Weight: 20kgs



Moving Head Beam – 7R

CH 1 – Colour Wheel

CH 2 – Strobe

CH 3 - Dimmer

CH 4 – Static gobo wheel

CH 5 – 16- facet Prism

CH 6 – 16- facet Prism Rotation

CH 7 - Reserved

CH 8 – Frost

CH 9 – Focus

CH 10 – Pan

CH 11 – Pan Fine

CH 12 – Tilt

CH 13 – Tilt Fine

CH 14 – Function

CH 15 – Reset

CH 16 – Lamp Control

Technical Specifications:

Electrical

- Power supply: Electronic auto-ranging
- Input voltage range: Supply 100-240V, 50/60Hz
- Power consumption: 230W
- Multi-wonderful effect.
- Smart bulb switch control

Operation

- Random strobe and pulse strobe optional
- Silent fans cooling
- Stand-alone operation



Available Models:

- LK MH 10R
- LK MH 15R
- LK MH 17R