

Product Model No. : LK P250 T/D

Product Description : LED Lens Panel 3200K /5600K 250W

High quality LED Lens Panel light with Controlled beam spread of 35 Degree provided with high purity parameters like CRI, TLCI & R9 Values above 96, Studio quality dimming from 100% ~ 0% along with Manual, DmX and Standalone modes of operation. Light is ideal to be used for Tv Studios Chroma and Anchor lighting application, Photography use, Film, Fiction requirement and multipurpose requirements.

Accessories: Barndoor, Diffuser, POS Yoke, Safety Chain, C Clamp

LED LENS PANEL 250W



Technical Specifications:

Electrical & Power:

- Power Consumption 260W
- Input Voltage AC 100V ~ 240V, 50Hz

Optical Arrangement:

- Beam Angle 35° Spread (Optional 60 Degree)
- Lens controlled Beam Angle 5x5 Array (PC Lens)

Lamp Source:

- LED SMD Lamp Source 5x5 Array
- CCT 3200K/5600K 600 x 0.5W Surface Mounted LED's
- Colour Rendering Index 98+
- Tel. Lighting Consistency Index 99+
- R9 Value 95+
- 50,000 Hours Burning life

Physical & Construction:

- Dimension 610 x 400 x 140mm
- Weight 11.2 Kgs/ 24.69 lbs
- DmX 5 Pin In and Out
- Power Loop In and Out
- Ingress Protection IP20
- Aluminium Body with Black Powder coated finish
- LCD Easy View Display
- Inbuilt Barndoor arrangement

Control:

- DmX 512 Through 5 Pin XLR
- Manual Mode Operation
- · 1 Channel DmX Control
- Master Slave mode through keys / pot








Others:


- Working Temperature +45° ~ -25°
- Passive Cooling System, No Fan
- Compatible for High Speed Photography 10K FPS





Tv Studio Lighting




250W LED LENS PANEL - 3200K / 5600K









3200K 5600K

Features



Power 260W



DMX 512

Control

Beam Angle

Power / DMX
In
Out


DMX Channels



CRI Value



Photometry Readings



Available Models:

- LK P250 T (Tungsten)
- LK P250 D (Daylight)
- LK P250 BC (Bi Color)

Fixture Images

