

260W Moving Head 10R Beam

Product Code : LK MH 10R
Product Description : Moving Head Beam – 10R

Moving Head Beam effect light 10R Base high bright strong beam, ideal for Stage Events, Auditorium Stages, Multipurpose application. Quick response to the control signal makes it unique. Excellent zoom range for beam angle varying from 0° ~ 3.8° to create effect of beam function



Lamp Source : MSD Yodn Lamp 260W 10R, 8500K
Electrical : AC 100-240V, 50/60HZ
Mode : 18 Channel DmX Control,
 Stand Alone, Test Mode & Master Slave

Technical Specifications:

Optic:

- Colour temperature: 8500K
- Ballast: Electronics ballast
- Gobo Wheel: 14 gobos + blank
- Pattern wheel: 14 fixed pattern piece + blank
- Prism: Rotating 8 Prism
- Dimming 0-100% Linear Adjustment
- Focus + Frost
- Beam angle : Parallel beam angle: 0-3.8

Motorized

- Pan/Tilt
- Pan movement range: 540°
- Tilt movement range: 270°
- Automatic Pan/Tilt position correction

Other

- LCD Easy view display
- Data DmX through 3 / 5 Pin XLR's
- IP20 rated product
- Efficient low noise fan cooling system
- International Standard DMX 512
- High temperature resistance plastic
- Overheating intelligent protection
- Net Weight 17Kgs



Moving Head Beam – 10R

CH 1 – Colour

CH 2 – Shutter

CH 3 - Dimmer

CH 4 – Gobo

CH 5 – Prism 1

CH 6 – Prism 1 Rot

CH 7 - Prism 2

CH 8 – Prism 2 Rot

CH 9 – Focus

CH 10 – Pan

CH 11 – Pan Low

CH 12 – Tilt

CH 13 – Tilt Low

CH 14 – P/T Speed

CH 15 – Frost

CH 16 – Qicai

CH 17 – Lamp

CH 18 – Reset


Technical Specifications:

Electrical

- Power supply: Electronic auto-ranging
- Input voltage range: Supply 100-240V, 50/60Hz
- Power consumption: 260W
- High speed strobe effect
- Smart bulb switch control

Operation

- Double chip Stroboscopic (0.5 ~ 9 times /SEC)
- Silent fans cooling
- Motor: Total 13 mute motor
- Stand-alone operation



Available Models:

- LK MH 7R
- LK MH 15R
- LK MH 17R