

350W Moving Head 15R Beam

Product Code : LK MH 15R
Product Description : Moving Head Beam – 15R

Moving Head Beam effect light 15R Base high bright strong beam, ideal for Stage Events, Auditorium Stages, Multipurpose application. Quick response to the control signal makes it unique. Excellent zoom range for beam angle varying from 0° ~ 3.8° to create effect of beam function.



Lamp Source : MSD Yodn Lamp 350W 15R, 8500K
Electrical : AC 100-240V, 50/60HZ
Mode : 16 Channel DmX Control,
Stand Alone, Test Mode & Master Slave

Technical Specifications:



Optic:

- Colour temperature: 8500K
- Ballast: Electronics ballast
- Gobo Wheel: 14 gobos + blank
- Pattern wheel: 14 fixed pattern piece + blank
- Prism: Rotating 8 Prism
- Dimming 0-100% Linear Adjustment
- Focus + Frost
- Beam angle : Parallel beam angle: 0-3.8

Motorized

- Pan/Tilt
- Pan movement range: 540°
- Tilt movement range: 270°
- Automatic Pan/Tilt position correction

Other

- LCD Easy view display
- Data DmX through 3 / 5 Pin XLR's
- IP20 rated product
- International Standard DMX 512
- High temperature resistance plastic
- Overheating intelligent protection
- Light body color: Black
- Net Weight 17Kgs



Moving Head Beam – 15R

CH 1 – Colour

CH 2 – Shutter

CH 3 - Dimmer

CH 4 – Gobo

CH 5 – Prism 1 Prism 2

CH 6 – Prism 1 Rotation

CH 7 - Prism 2 Rotation

CH 8 – Focus

CH 9 – X- Axis

CH 10 – X- Axis fine tuning

CH 11 – Y- Axis

CH 12 – Y – Axis fine tuning

CH 13 – XY velocity

CH 14 – Atomization

CH 15 – colorful

CH 16 – Light the lights out Reset

Technical Specifications:

Electrical

- Power supply: Electronic auto-ranging
- Input voltage range: Supply 100-240V, 50/60Hz
- Total power: 420W
- High speed strobe effect
- Smart bulb switch control
- Average life span: 2000H

Operation

- Double chip Stroboscopic (0.5 ~ 9 times /SEC)
- Silent fans cooling
- Motor: Total 13 mute motor
- Stand-alone operation



Available Models:

- LK MH 7R
- LK MH 10R
- LK MH 12R
- LK MH 17R