

Product Model No. : LK PXL 0.5 - 10

Product Description : 10W RGBW LED
PIXEL BAR



Facade Lighting breathes life into unique facades & architecture in private or public spaces. It can also be used to add an artistic feel to the exteriors with shadows, also use up-lighting for pillars and columns to add a simple contrast or to accentuate the object for making it the centre of attraction

10W LED PIXEL BAR LIGHT

Technical Specifications:

Electrical & Power:

- Power Consumption : 10W
- Input Power : DC 24V

Optical Arrangement:

- Beam Angle : 120°
- Field Angle : 140°

Lamp Source:

- LED Source : SMD 5050
- Colour Temperature : RGBW(4 in 1)
- No of LEDs : 30 Nos
- No of Pixels : 5 Nos
- LED Hours Burning life : 50,000

Control & Others:

- Control Option : DmX 512 / Auto Mode
- DmX Channels : 4 DmX
- Working Temperature : +55° ~ -30°
- SDCM : < 5
- Power Factor (Min) : 0.9
- Driver/power unit : External Power Supply

Physical & Construction:

- Dimension : 30 x 34 x 517mm
- Ingress Protection : IP66 Rated
- Body Housing : Extruded Aluminium
- Body Colour : White / Grey / Custom
- Mounting Type : Bracket mount
- Impact Resistance : IK05
- Cooling : Passive Cooling System

Dimensions:




Features



10W Power Consumption



DMX control



SMD Based LEDs



Beam angle: 120°



Colour Temperature: RGBW



IP 66 Water & Dust Resistance