

Product Model No. : LK LW 07 - 15

Product Description : 15W LED Linear Profile Light

Façade Lighting breathes life into unique facades & architecture in private or public spaces. This spot light adds an artistic feel to the exterior architecture & also used as an up-lighting for pillars and columns to add a simple contrast or to accentuate the object for making it the centre of attraction



15W LED LINEAR PROFILE LIGHT

Technical Specifications:

Electrical & Power:

- Power Consumption : 15W
- Input Voltage/Current : DC 24V / 500 mA
- Electrical Class : III Class
- Power Factor (Min) : 0.9
- Harmonic Distortion : < 10%
- Driver/power unit : External

Optical Arrangement:

- Beam Angle : 120°

Lamp Source:

- LED Source : SMD Based
- Available CCT : 3000K, 4000K, 5700K.
- CRI (Ra) : >80 (90 CRI –On Request)
- Lumens/W : > 65
- Net Luminous Flux : 975lm
- SDCM : < 3
- LED Hours Burning life : 50,000

Physical & Construction:

- Dimension : 1000 x 35 x 15mm
- Ingress Protection : IP66 Rated
- Body Housing : Aluminium Die Casted
- Body Colour : Black / Grey
- Mounting Type : Yoke Mount
- Impact Resistance : IK05
- Connector : M/F Cable Mount
- Working Temperature : +55° ~ -30°

Dimensions:



Control & Others:

- Control Option : On / Off


Features



15W Power Consumption



Simple On / Off control



SMD Based LEDs



Test Certificates



Beam angle: 120°



Color Temperature: 3000K




Ingress Protection: IP 66




Impact Protection: IK 05

Photometric Data



Light Distribution chart



Chromaticity Report

Distance IN (MTRS)	Beam Width		Lux (Center)
	W (MTRS)	H (MTRS)	
1	3.4641	1	129
2	6.9282	2	32.2
3	10.3923	3	15
4	13.8564	4	9
5	17.3205	5	6
6	20.7846	6	5
7	24.2487	7	4
8	27.7128	8	4
9	31.1769	9	4
10	34.6410	10	4

Vertical Spread : 120 Deg. Horizontal Spread : 120 Deg.

Lux level distribution (120°)

Certifications



© 2023 Leksa Lighting All rights reserved. Leksa Lighting does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial or and does not form part of any quotation or contract, unless otherwise agreed by Leksa Lighting. Leksa logo is registered trademark of Leksa Lighting Technologies Private Limited.

www.leksalighting.com

biz@leksalighting.com