

**Product Model No.** : LK PXL 11 - 20  
**Product Description** : 20W RGBW LED  
 PIXEL BAR



Facade Lighting breathes life into unique facades & architecture in private or public spaces. It can also be used to add an artistic feel to the exteriors with shadows, also use up-lighting for pillars and columns to add a simple contrast or to accentuate the object for making it the centre of attraction

## 20W LED PIXEL BAR LIGHT

### Technical Specifications:

#### Electrical & Power:

- Power Consumption : 20W
- Input Power : DC 24V

#### Optical Arrangement:

- Beam Angle : 120°
- Field Angle : 140°

#### Lamp Source:

- LED Source : SMD 5050
- Colour Temperature : RGBW(4 in 1)
- No of LEDs : 60 Nos
- No of Pixels : 10 Nos
- LED Hours Burning life : 50,000

#### Control & Others:

- Control Option : DmX 512 / Auto Mode
- DmX Channels : 4 DmX
- Working Temperature : +55° ~ -30°
- SDCM : < 5
- Power Factor (Min) : 0.9
- Driver/power unit : External Power Supply

#### Physical & Construction:

- Dimension : 30 x 34x 1017mm
- Ingress Protection : IP66 Rated
- Body Housing : Extruded Aluminium
- Body Colour : White /Grey/Custom
- Mounting Type : Bracket mount
- Impact Resistance : IK05
- Cooling : Passive Cooling System

#### Dimensions:




### Features



20W Power Consumption



DMX control



SMD Based LEDs



Beam angle: 120°



Colour Temperature: RGBW



IP 66 Water & Dust Resistance