

L E K S A

# SOFT PANEL

L I G H T



L E K S A

# BEBBLE PANEL

L I G H T



These lights are essential tools in modern filmmaking and photography. These LED fixtures provide soft, diffused illumination, reducing harsh shadows and creating a flattering look for subjects. Their slim design, adjustable color temperature, and brightness make them adaptable for various shooting situations, contributing to high-quality visuals.

# SOFT PANEL SERIES



# BEBBLE PANEL

0-100%  
Dimming

3200K/5600K  
Bi-Color (3200K-5600K)

120°/60°

IP20



Available models

SOFT PANEL  
100W

SOFT PANEL  
150W

SOFT PANEL  
200W

SOFT PANEL  
250W

SOFT PANEL  
300W

BEBBLE PANEL  
200W

## Main Features

- Power Loop In & Power Loop Out option available
- LCD Easy View Display
- Light Compatible upto 10K FPS Shoots
- Flicker Free Linear Dimming with CCT Tuning Options
- Master Slave Mode for Easy Control of Multiple Lights
- Multiple Accessories Options - Barndoor, Softbox, Stand, C Clamp, Safety Bond



## Specifications: BEBBLE PANEL

Rated Input Voltage	AC 220-240V, 50/60Hz
System Wattage	200W
Beam Angle of Light	60°
CCT Range	3000K- 6000K
CRI	>98
TLCI	>98
R9	>95
LED Life	50000 Burning hours
LED Efficacy / Lumen	110 Lm/W, 22000 Lumen
Control	Manual (Knob & Key) & DMX 512
Key Setting	ON/OFF, Brightness from 0-100% adjustment, CCT adjustment from 3000K to 6000K
Product Size	475 x 380 x 165 mm
Product Weight	8 kgs
Lamp Body Color	Black
Housing/Body	Mild Steel & Extruded Aluminium
Protection Rating	IP20

## Accessories



Stand



Power Cord




Spud



C Clamp



Safety Bond



Barndoor

## Main Features

- Power Loop In & Power Loop Out option available
- LCD Easy View Display
- Flicker Free Linear Dimming with seamless CCT adjustment Options
- Master Slave Mode and app control for Easy Control of Multiple Lights
- Multiple Accessories Options - Barndoor, Softbox, Stand, C Clamp, Safety Bond, Honeycomb, POS Yoke



## Specifications: SOFT PANEL

Rated Input Voltage	AC 220-240V, 50/60Hz
System Wattage	100W (Other Models - 150W/200W/250W/300W)
Beam Angle of Light	120°
CCT Range	3200K/5600K/ Bi-Color (3200K-5600K)
CRI	>98
TLCI	>99
R9	>95
LED Life	50000 Burning hours
LED Efficacy / Lumen	110 Lm/W, 11000 Lumen
Control	Manual (Knob & Key) & DMX 512 / App
Key Setting	ON/OFF, Brightness from 0-100% adjustment
Product Size	450 x 400 x 140 mm
Product Weight	7.25 kgs
Lamp Body Color	Black/Custom
Housing/Body	Mild Steel & Extruded Aluminium
Protection Rating	IP20

## Accessories

