

**LEKSPRIME**

# HIGH END INDOOR DIE CAST SERIES

**P1.9**



Elevate your indoor space with Leksa LED walls that deliver vibrant, high-resolution visuals perfect for indoor spaces, conference rooms, control rooms, shopping malls, auditoriums etc. Our Led wall provides sharp, eye-catching content that captivates audiences. Built for energy, efficiency and durability, our indoor LED walls offer seamless performance and stunning clarity to enhance brand presence and engage viewers like never before.



Brightness  
600



Cabinet size  
500x500



Wide viewing  
angle



Rear  
Maintenance



Input power  
AC150~240V



Refresh rate  
3840 (Hz)



Strong Build

## PRODUCT SPECIFICATIONS

LED	SMD1515	Colour temperature (K)	2500~10000
Module size (mm)	250x250	Horizontal viewing angle (°)	≥ 160
Module resolution (WxH)	128x128	Vertical viewing angle (°)	≥ 160
Cabinet size (mm)	500x500	Max power consumption (W/m <sup>2</sup> )	800
Maintenance method	Rear	Ave.power consumption (W/m <sup>2</sup> )	350
Cabinet Weight(kg)	6.5	Contrast ratio	6000:1
Pixel density (Dots/m <sup>2</sup> )	2,62,144	Working temperature (°C)	0~40
Brightness(Nits)	600	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	0 ~ 65
Grey level (Bit)	12~16	Life time (hrs)	50,000

# HIGH END INDOOR DIE CAST SERIES

## P2.6



Elevate your indoor space with Leksa LED walls that deliver vibrant, high-resolution visuals perfect for indoor spaces, conference rooms, control rooms, shopping malls, auditoriums etc. Our Led wall provides sharp, eye-catching content that captivates audiences. Built for energy, efficiency and durability, our indoor LED walls offer seamless performance and stunning clarity to enhance brand presence and engage viewers like never before.



Brightness  
600



Cabinet size  
500x500



Wide viewing  
angle



Rear  
Maintenance



Input power  
AC150~240V



Refresh rate  
3840 (Hz)



Strong Build

### PRODUCT SPECIFICATIONS

<b>LED</b>	SMD1515	<b>Colour temperature (K)</b>	2500~10000
<b>Module size (mm)</b>	250x250	<b>Horizontal viewing angle (°)</b>	≥ 160
<b>Module resolution (WxH)</b>	96x96	<b>Vertical viewing angle (°)</b>	≥ 160
<b>Cabinet size (mm)</b>	500x500	<b>Max power consumption (W/m²)</b>	600
<b>Maintenance method</b>	Rear	<b>Ave.power consumption (W/m²)</b>	200
<b>Cabinet Weight(kg)</b>	6.5	<b>Contrast ratio</b>	6000:1
<b>Pixel density (Dots/m²)</b>	1,47,456	<b>Working temperature (°C)</b>	0~40
<b>Brightness(Nits)</b>	600	<b>Brightness adjustment</b>	Manual
<b>Refresh rate (Hz)</b>	3840	<b>Storage humidity (°C)</b>	0 ~ 65
<b>Grey level (Bit)</b>	12~16	<b>Life time (hrs)</b>	50,000



# HIGH END INDOOR DIE CAST SERIES

## P2.9



Elevate your indoor space with Leksa LED walls that deliver vibrant, high-resolution visuals perfect for indoor spaces, conference rooms, control rooms, shopping malls, auditoriums etc. Our Led wall provides sharp, eye-catching content that captivates audiences. Built for energy, efficiency and durability, our indoor LED walls offer seamless performance and stunning clarity to enhance brand presence and engage viewers like never before.



Brightness  
600



Cabinet size  
500x500



Wide viewing  
angle



Rear  
Maintenance



Input power  
AC150~240V



Refresh rate  
3840 (Hz)



Strong Build

### PRODUCT SPECIFICATIONS

LED	SMD2020	Colour temperature (K)	2500~10000
Module size (mm)	250x250	Horizontal viewing angle (°)	≥ 160
Module resolution (WxH)	84x84	Vertical viewing angle (°)	≥ 160
Cabinet size (mm)	500x500	Max power consumption (W/m <sup>2</sup> )	480
Maintenance method	Rear	Ave.power consumption (W/m <sup>2</sup> )	184
Cabinet Weight(kg)	6.5	Contrast ratio	6000:1
Pixel density (Dots/m <sup>2</sup> )	1,12,896	Working temperature (°C)	0~40
Brightness(Nits)	600	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	0 ~ 65
Grey level (Bit)	12~16	Life time (hrs)	50,000

**LEKSPRIME**

# HIGH END INDOOR DIE CAST SERIES

**P3.9**



Elevate your indoor space with Leksa LED walls that deliver vibrant, high-resolution visuals perfect for indoor spaces, conference rooms, control rooms, shopping malls, auditoriums etc. Our Led wall provides sharp, eye-catching content that captivates audiences. Built for energy, efficiency and durability, our indoor LED walls offer seamless performance and stunning clarity to enhance brand presence and engage viewers like never before.



Brightness  
600



Cabinet size  
500x500



Wide viewing  
angle



Rear  
Maintenance



Input power  
AC150~240V



Refresh rate  
3840 (Hz)



Strong Build

## PRODUCT SPECIFICATIONS

LED	SMD2020	Colour temperature (K)	2500~10000
Module size (mm)	250x250	Horizontal viewing angle (°)	≥ 160
Module resolution (WxH)	64x64	Vertical viewing angle (°)	≥ 160
Cabinet size (mm)	500x500	Max power consumption (W/m <sup>2</sup> )	500
Maintenance method	Rear	Ave.power consumption (W/m <sup>2</sup> )	200
Cabinet Weight(kg)	6.5	Contrast ratio	6000:1
Pixel density (Dots/m <sup>2</sup> )	65,536	Working temperature (°C)	0~40
Brightness(Nits)	600	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	0 ~ 65
Grey level (Bit)	12~16	Life time (hrs)	50,000



**LEKSPRIME**

# HIGH END INDOOR DIE CAST SERIES

**P4.8**



Elevate your indoor space with Leksa LED walls that deliver vibrant, high-resolution visuals perfect for indoor spaces, conference rooms, control rooms, shopping malls, auditoriums etc. Our Led wall provides sharp, eye-catching content that captivates audiences. Built for energy, efficiency and durability, our indoor LED walls offer seamless performance and stunning clarity to enhance brand presence and engage viewers like never before.



Brightness  
600



Cabinet size  
500x500



Wide viewing  
angle



Rear  
Maintenance



Input power  
AC150~240V



Refresh rate  
3840 (Hz)



Strong Build

## PRODUCT SPECIFICATIONS

LED	SMD2020	Colour temperature (K)	2500~10000
Module size (mm)	250x250	Horizontal viewing angle (°)	≥ 160
Module resolution (WxH)	52x52	Vertical viewing angle (°)	≥ 160
Cabinet size (mm)	500x500	Max power consumption (W/m <sup>2</sup> )	460
Maintenance method	Rear	Ave.power consumption (W/m <sup>2</sup> )	160
Cabinet Weight(kg)	6.5	Contrast ratio	6000:1
Pixel density (Dots/m <sup>2</sup> )	43,264	Working temperature (°C)	0~40
Brightness(Nits)	600	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	0 ~ 65
Grey level (Bit)	12~16	Life time (hrs)	50,000