

LEKSWALL

HIGH END OUTDOOR DIE CAST SERIES

P2.9



Put your brand in the spotlight with our ultra-bright LED Video wall. Built to perform brilliantly even in direct sunlight. Whether it's for advertising, live events, retail exteriors or public spaces. Our video walls deliver vivid colors, seamless scalability, and dynamic content control. Instantly update your content from anywhere to keep your audience engaged and your message fresh. Turn any outdoor space into an unforgettable visual experience and let your brand shine



Brightness
≥4500



Cabinet size
1000x1000



Wide viewing
angle



Front & Rear
Maintenance



Input power
AC150~240V



Refresh rate
3840 (Hz)



Strong Build



IP65 Rating

PRODUCT SPECIFICATIONS

LED	SMD1415	Colour temperature (K)	1000~18500
Module size (mm)	500x250	Horizontal viewing angle (°)	140
Module resolution (WxH)	168x84	Vertical viewing angle (°)	160
Cabinet size (mm)	1000x1000	Max power consumption (W/m ²)	810
Maintenance method	Front & Rear	Ave.power consumption (W/m ²)	270
Cabinet Weight(kg)	22.5	Contrast ratio	60000:1
Pixel density (Dots/m ²)	1,12,896	Working temperature (°C)	-20~60
Brightness(Nits)	≥4500	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	-20~60
Grey level (Bit)	16	Life time (hrs)	50,000

LEKSWALL

HIGH END OUTDOOR DIE CAST SERIES

P3.9



Put your brand in the spotlight with our ultra-bright LED Video wall. Built to perform brilliantly even in direct sunlight. Whether it's for advertising, live events, retail exteriors or public spaces. Our video walls deliver vivid colors, seamless scalability, and dynamic content control. Instantly update your content from anywhere to keep your audience engaged and your message fresh. Turn any outdoor space into an unforgettable visual experience and let your brand shine



Brightness
6000



Cabinet size
1000x1000



Wide viewing
angle



Front & Rear
Maintenance



Input power
AC150~240V



Refresh rate
3840 (Hz)



Strong Build



IP65 Rating

PRODUCT SPECIFICATIONS

LED	SMD1921	Colour temperature (K)	1000~18500
Module size (mm)	500x250	Horizontal viewing angle (°)	140
Module resolution (WxH)	128x64	Vertical viewing angle (°)	160
Cabinet size (mm)	1000x1000	Max power consumption (W/m ²)	780
Maintenance method	Front & Rear	Ave.power consumption (W/m ²)	260
Cabinet Weight(kg)	22.5	Contrast ratio	10000:1
Pixel density (Dots/m ²)	65,536	Working temperature (°C)	-20~60
Brightness(Nits)	6000	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	-20~60
Grey level (Bit)	16	Life time (hrs)	50,000

LEKSWALL

HIGH END OUTDOOR DIE CAST SERIES

P4.8



Put your brand in the spotlight with our ultra-bright LED Video wall. Built to perform brilliantly even in direct sunlight. Whether it's for advertising, live events, retail exteriors or public spaces. Our video walls deliver vivid colors, seamless scalability, and dynamic content control. Instantly update your content from anywhere to keep your audience engaged and your message fresh. Turn any outdoor space into an unforgettable visual experience and let your brand shine



Brightness
60000



Cabinet size
1000x1000



Wide viewing
angle



Front & Rear
Maintenance



Input power
AC150~240V



Refresh rate
3840 (Hz)



Strong Build



IP65 Rating

PRODUCT SPECIFICATIONS

LED	SMD1921	Colour temperature (K)	1000~18500
Module size (mm)	500x250	Horizontal viewing angle (°)	140
Module resolution (WxH)	104x52	Vertical viewing angle (°)	160
Cabinet size (mm)	1000x1000	Max power consumption (W/m ²)	850
Maintenance method	Front & Rear	Ave.power consumption (W/m ²)	283
Cabinet Weight(kg)	22.5	Contrast ratio	10000:1
Pixel density (Dots/m ²)	43,264	Working temperature (°C)	-20~60
Brightness(Nits)	6000	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	-20~60
Grey level (Bit)	16	Life time (hrs)	50,000

LEKSWALL

HIGH END OUTDOOR DIE CAST SERIES

P6.2



Put your brand in the spotlight with our ultra-bright LED Video wall. Built to perform brilliantly even in direct sunlight. Whether it's for advertising, live events, retail exteriors or public spaces. Our video walls deliver vivid colors, seamless scalability, and dynamic content control. Instantly update your content from anywhere to keep your audience engaged and your message fresh. Turn any outdoor space into an unforgettable visual experience and let your brand shine



Brightness
6000



Cabinet size
1000x1000



Wide viewing
angle



Front & Rear
Maintenance



Input power
AC150~240V



Refresh rate
3840 (Hz)



Strong Build



IP65 Rating

PRODUCT SPECIFICATIONS

LED	SMD2727	Colour temperature (K)	1000~18500
Module size (mm)	500x250	Horizontal viewing angle (°)	140
Module resolution (WxH)	80x40	Vertical viewing angle (°)	160
Cabinet size (mm)	1000x1000	Max power consumption (W/m ²)	800
Maintenance method	Front & Rear	Ave.power consumption (W/m ²)	270
Cabinet Weight(kg)	22.5	Contrast ratio	10000:1
Pixel density (Dots/m ²)	25,600	Working temperature (°C)	-20~60
Brightness(Nits)	6000	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	-20~60
Grey level (Bit)	16	Life time (hrs)	50,000

LEKSWALL

HIGH END OUTDOOR DIE CAST SERIES

P7.8



Put your brand in the spotlight with our ultra-bright LED Video wall. Built to perform brilliantly even in direct sunlight. Whether it's for advertising, live events, retail exteriors or public spaces. Our video walls deliver vivid colors, seamless scalability, and dynamic content control. Instantly update your content from anywhere to keep your audience engaged and your message fresh. Turn any outdoor space into an unforgettable visual experience and let your brand shine



Brightness
6000



Cabinet size
1000x1000



Wide viewing
angle



Front & Rear
Maintenance



Input power
AC150~240V



Refresh rate
3840 (Hz)



Strong Build



IP65 Rating

PRODUCT SPECIFICATIONS

LED	SMD2727	Colour temperature (K)	1000~18500
Module size (mm)	500x250	Horizontal viewing angle (°)	140
Module resolution (WxH)	64x32	Vertical viewing angle (°)	160
Cabinet size (mm)	1000x1000	Max power consumption (W/m ²)	780
Maintenance method	Front & Rear	Ave.power consumption (W/m ²)	260
Cabinet Weight(kg)	22.5	Contrast ratio	10000:1
Pixel density (Dots/m ²)	16384	Working temperature (°C)	-20~60
Brightness(Nits)	6000	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	-20~60
Grey level (Bit)	16	Life time (hrs)	50,000

LEKSWALL

HIGH END OUTDOOR DIE CAST SERIES

P10.4



Put your brand in the spotlight with our ultra-bright LED Video wall. Built to perform brilliantly even in direct sunlight. Whether it's for advertising, live events, retail exteriors or public spaces. Our video walls deliver vivid colors, seamless scalability, and dynamic content control. Instantly update your content from anywhere to keep your audience engaged and your message fresh. Turn any outdoor space into an unforgettable visual experience and let your brand shine



Brightness
6000



Cabinet size
1000x1000



Wide viewing
angle



Front & Rear
Maintenance



Input power
AC150~240V



Refresh rate
3840 (Hz)



Strong Build



IP65 Rating

PRODUCT SPECIFICATIONS

LED	SMD2727	Colour temperature (K)	1000~18500
Module size (mm)	500x250	Horizontal viewing angle (°)	140
Module resolution (WxH)	48x24	Vertical viewing angle (°)	160
Cabinet size (mm)	1000x1000	Max power consumption (W/m ²)	780
Maintenance method	Front & Rear	Ave.power consumption (W/m ²)	260
Cabinet Weight(kg)	22.5	Contrast ratio	10000:1
Pixel density (Dots/m ²)	9216	Working temperature (°C)	-20~60
Brightness(Nits)	6000	Brightness adjustment	Manual
Refresh rate (Hz)	3840	Storage humidity (°C)	-20~60
Grey level (Bit)	16	Life time (hrs)	50,000