

Product Model No. : LK SG 200 T/D
Product Description : 200W LED linear Blinder Light
4X50

SOFT GLO – 200W SC

High bright uniform distributed 50W Each LED Source for illuminating the multipurpose venues, large audience, Auditorium Stages, DJ & Event Stages, Large photographic venues, Production Studios, Discotheques, Film & Band performances for providing flood lighting effect.



Accessories: Safety Chain, C Clamp

Technical Specifications:

Electrical & Power:

- Power Consumption 200W
- Input Voltage AC 100V ~ 240V, 50Hz

Optical Arrangement:

- Beam Angle 25°/ 45°

Lamp Source:

- LED COB Based Source
- 3200K/5600K, 4 x 50W Chip on Board
- Colour Rendering Index 95+
- Tel. Lighting Consistency Index 95+
- R9 Value 90+
- 50,000 Hours Burning life

Physical & Construction:

- Dimension 370x 175x 175mm
- Weight 3.95 Kgs
- DmX 3/5 Pin In and Out
- Power Loop In and Out
- Ingress Protection IP20
- MS Body with Black Powder coated finish
- LED Easy View Display

Control:

- DmX 512 Through 5 Pin XLR
- 2/6 Channel DmX Control
- Manual Mode Operation
- Sound Active Mode Control
- Master Slave Mode




Others:

- Working Temperature +45° ~ -30°
- Strobe option Adjustable 1~25 times/Sec Variable
- 11.7KHz Refresh Rate




Stage Effect Illumination

200W LED LINEAR BLINDER LIGHT



3200K



Features

Lamp Source




CC Temp.



Beam Angle



DMX Channels



Power



Control



Power/DMX



CRI Value



Photometry Readings

LINEAR BLINDER 200W

Distance in Mtrs

2M 4M 6M 8M 10M

1 FC = 10.8 Lux Output in Lux



Intensity in Lux 3200K (25°)	20100	5025	2234	1257	805
Intensity in Lux 5600K (25°)	21158	5289	2352	1323	847

Available Models:

- LK SG 200T
- LK SG 200D

Fixture Images



View-1



View-2



View-3



View-4